

Specifications\*

MODEL	SB22m	SB25h	SB31m	SB31h	
<b>ENGINE (DIESEL)</b>					
Model	A1100N3	A1100N2	A1100T1		
Type	Water cooled 3-cylinder diesel, STAGE V		Water cooled 3-cylinder diesel		
Displacement (cc)	1058	1175			
Engine gross power (HP/ kW)	21/ 15.3	24/ 17.9	30/ 23.2	30/ 23.2	
Rated speed (rpm.)	2600				
Fuel tank capacity (l.)	23				
Combustion system	Indirect				
Battery (V.)	12				
Air cleaner	Dry, element				
<b>TRAVELLING SYSTEM</b>					
Transmission	Mechanical	Hydrostatic	Mechanical	Hydrostatic	
Groups	6 F / 2 R	2	6 F / 2 R	2	
Max. forward speed (km/h)	19	21.4	21,9	24,6	
Drive system	4 wheel drive				
Clutch	Dry, single plate				
Brake	Wet, multidisc				
Sperddifferential	Rear				
<b>TIRES</b>					
Agri	Front	6-12	6-12	7-16	7-16
	Rear	9.5-16	9.5-16	11.2-20	11.2-20
Turf	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5
Industry	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	12-16.5	12-16.5	12-16.5	12-16.5
<b>PTO</b>					
Rear PTO (rpm.)	540 and 960				
Mid PTO (rpm.)	2600				
<b>HYDRAULIC SYSTEM</b>					
Main (lpm.)	18.2				
Steering (lpm.)	13				
Steering category	Power Assisted Hydrostatic				
Control type	Position				
Remote control valve	2 double acting rear				
Hitch category	Cat. 1				
Max. lift capacity (kg)	650				
<b>DIMENSIONS</b>					
Length (mm)	3066		3122		
Width (mm)	1124		1369		
Height (mm)	2216		2330		
Ground clearance (mm)	315		407		
Wheelbase (mm)	1502		1670		
Weight incl. ROPS (kg)	770	780	885	908	

\*The specifications are subject to change without notice.

COMPACT TRACTOR

SB22-25-31

SHIBAURA



**Important information**

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



**SHIBAURA EUROPE BV**  
 Begonialaan 7  
 NL - 6851 TE Huissen  
 T. 0031 (0)26 326 9999  
 F. 0031 (0)26 326 9990  
 E. info@shibaaura.com  
 I. www.shibaaura.com

Dealer:

### DASHBOARD



Clear visibility of dashboard allows easy monitoring of the tractor's condition: rated speed, temperature and tank capacity.

### FRONT LIFT



Frontlift cat. 0 with a lift capacity of 700 kg.

### PTO LEVER



Easy to use PTO comes standard with 2 speeds rear and 1 speed mid.

### PEDALS



Hydrostatic control pedals for smooth handsfree forward & reverse motion (hst-models).



### ENGINE



3-cylinder diesel engine delivers the highest power in its class with outstanding durability and reliability. The engines of SB22 and SB25 comply with the Stage V emission standard.

### SEAT



The operating levers are placed within easy reach on the left and right of the seat for ergonomic operation.

### 3-POINT HITCH



3-point hitch rear Category I provides a lift capacity of 650 kg.

### TIRES



Industrial-, agricultural- and turf tires.