

Specifications*

MODEL		SB22m	SB25h	SB31m	SB31h
ENGINE (DIESEL)					
Model		A1100N3	A1100N2	A1100T1	
Type		Water cooled 3-cylinder diesel, STAGE V		Water cooled 3-cylinder diesel	
Displacement (cc)		1058		1175	
Engine gross power (HP/ kW)		21/ 15.3	24/ 17.9	30/ 23.2	30/ 23.2
Rated speed (rpm.)		2600			
Fuel tank capacity (l.)		23			
Combustion system		Indirect			
Battery (V.)		12			
Air cleaner		Dry, element			
TRAVELLING SYSTEM					
Transmission		Mechanical	Hydrostatic	Mechanical	Hydrostatic
Groups		6 F / 2 R	2	6 F / 2 R	2
Max. forward speed (km/h)		19	21.4	21,9	24,6
Drive system		4 wheel drive			
Clutch		Dry, single plate			
Brake		Wet, multidisc			
Sperddifferential		Rear			
TIRES					
Agri	Front	6-12	6-12	7-16	7-16
	Rear	9.5-16	9.5-16	11.2-20	11.2-20
Turf	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5	33x12.5-16.5
Industry	Front	23x8.5x12	23x8.5x12	23x8.5x12	23x8.5x12
	Rear	12-16.5	12-16.5	12-16.5	12-16.5
PTO					
Rear PTO (rpm.)		540 and 960			
Mid PTO (rpm.)		2600			
HYDRAULIC SYSTEM					
Main (lpm.)		18.2			
Steering (lpm.)		13			
Steering category		Power Assisted Hydrostatic			
Control type		Position			
Remote control valve		2 double acting rear			
Hitch category		Cat. 1			
Max. lift capacity (kg)		650			
DIMENSIONS					
Length (mm)		3066		3122	
Width (mm)		1124		1369	
Height (mm)		2216		2330	
Ground clearance (mm)		315		407	
Wheelbase (mm)		1502		1670	
Weight incl. ROPS (kg)		770	780	885	908

*The specifications are subject to change without notice.



Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.

SHIBAURA

SHIBAURA EUROPE BV

Begonialaan 7

NL - 6851 TE Huissen

T. 0031 (0)26 326 9999

F. 0031 (0)26 326 9990

E. info@shibaura.com

I. www.shibaura.com

Dealer:

DASHBOARD



Clear visibility of dashboard allows easy monitoring of the tractor's condition: rated speed, temperature and tank capacity.

FRONT LIFT



Frontlift cat. 0 with a lift capacity of 700 kg.

PTO LEVER



Easy to use PTO comes standard with 2 speeds rear and 1 speed mid.

PEDALS



Hydrostatic control pedals for smooth handsfree forward & reverse motion (hst-models).



ENGINE



3-cylinder diesel engine delivers the highest power in its class with outstanding durability and reliability. The engines of SB22 and SB25 comply with the Stage V emission standard.

SEAT



The operating levers are placed within easy reach on the left and right of the seat for ergonomic operation.

3-POINT HITCH



3-point hitch rear Category I provides a lift capacity of 650 kg.

TIRES



Industrial-, agricultural- and turf tires.