

Turbo 440 D

**Gianni
Ferrari**





GTM - GSM
15,5-16 hp



GTR
16-21 hp



GTS
22-23 hp



GT
28 hp



TURBO Z
22-40 hp



TURBOGRASS
22-23 hp



PG - SR
22-28 hp



TURBO 1-1W-2-4
28-50 hp



TURBOLOADER
22-44 hp

TECHNICAL FEATURES

▶ Modello	Turbo Z 440 D	
▶ Engine	Fuel Diesel Model Kubota V1505-T Power / Displacement 40 hp / 1.498 cc. No. Cylinders / Cooling 4 / Liquid Fittings Pressure lubrication system with gear pump – cyclone-type air filter – fuel filter Fuel tank capacity 43 L	
▶ Hydrostatic transmission	Pumps Danfoss variable displacement axial piston pumps Motors Danfoss axial piston motors on reduction gears Driving wheels 2WD Max forward speed 18 km/h Driving system Zero Turning Radius (ZTR) 2 control levers with Easy Control Panel (ECP™) Brakes Hydrostatic service brake (neutral position). Dual disc parking brake on transmission	
▶ Seat	Model Delux Grammer seat with lumbar support and headrest. Adjustable armrest and backrest Seat suspension Parallelogram suspension with 3 adjustable height position and driver's weight adjustment (50 kg to 130 kg)	
▶ Wheels/Tyres	Front Turf tyres 24 x 12.00 - 12 Front bar tread tyres (optional) 24 x 12.00 - 12 Oscillating rear axle 13 x 6.50 - 6	
▶ Power Take-Off	Type / Engagement Mechanical, with PTO shaft / Electric engagement by PTO button	
▶ Front lift	Type Hydraulic with 2 hydraulic rams	
▶ Electrical system	Battery 12 V / 70 Ah – battery isolator master switch as standard Safety sensors EEC European Standard / ISO Standard equipment Hour meter – coolant temperature Warning system Engine oil pressure – coolant temperature – battery (alternator fault) – glowplug – parking brake On-road use equipment As standard	
▶ Weight and measures (tractor unit only, basic version)	Unloaded weight 800 kg Length / Width / Height 247 x 142 x 132 (200)* cm	

* with ROPS folded down (upright)

The availability of models, versions and trim may vary depending on the country.

ATTACHMENTS

▶ 160 Dual-Cut™ mulching / rear discharge deck	Cutting width / No. Blades 155 cm (61") / 3 blades Cutting height adjustment Quick adjustment with SA™ lever, 2 cm to 8 cm Vertical position Hydraulic Weight 200 kg	
▶ Side discharge deck	Cutting width / No. Blades 150 cm (59") / 3 blades Cutting height adjustment Quick adjustment with SA™ lever, 2 cm to 8 cm Vertical position Hydraulic Weight 140 kg	
▶ Rear discharge deck	Cutting width / No. Blades 165 cm (65") / 4 blades Cutting height adjustment Quick adjustment with SA™ lever, 2 cm to 8 cm Vertical position Hydraulic Weight 190 kg	
▶ Flail mower	Cutting width / Blade reel 150 cm (59") / 100 flails (50 pairs) Cutting height adjustment 2 cm to 9 cm Weight 240 kg	
▶ Aerator / dethatcher	Working width / Blade reel 100 cm (40") / 28 mobile blades Weight 90 kg	
▶ Snow blade	Working width / Angling 175 cm (69") / ± 30°, hydraulic Weight 140 kg	

