

Specifications\*

MODEL	SB36h	SB47h
<b>ENGINE (DIESEL)</b>		
Model	A1700N4	A1700T2
Type	Water cooled 3-cylinder diesel	
Displacement (cc)	1714	1714
Engine gross power (HP/ kW)	35/ 25.7	45.5/ 33.5
Rated speed (rpm.)	2600	
Fuel tank capacity (l.)	27	
Combustion system	Indirect	
Battery (V.)	12	
Air cleaner	Dry, element	
<b>TRAVELLING SYSTEM</b>		
Transmission	Hydrostatic	
Groups	3	
Max. forward speed (km/h)	33	
Drive system	4 Wheel Drive	
Brake	Wet, multidisc	
Sperddifferential	Rear	
<b>TIRES</b>		
Agri	Front	ROPS: 8-16 / Cabin: 7-16
	Rear	ROPS: 12.4-24 / Cabin: 11,2 -24
Turf	Front	27x8.5x15
	Rear	41x14-20
Industry	Front	ROPS: 10x16.5 / Cabin: 24x8.5-14
	Rear	ROPS: 420/70-24 / Cabin: 15-19.5
<b>PTO</b>		
Rear PTO (rpm.)	independent, 560 and 780	
<b>HYDRAULIC SYSTEM</b>		
Main (lpm.)	33.6	
Steering (lpm.)	18	
Steering category	Power Assisted Hydrostatic	
Control type	Position / Draft	
Remote Control valve	1 double acting rear	
Hitch category	Cat. 1	
Max. lift capacity (kg)	1650	
<b>DIMENSIONS</b>		
Length (mm)	3096	
Width (mm)	1451	
Height (mm)	2643	
Ground clearance (mm)	335	
Wheelbase (mm)	1671	
Weight incl. ROPS (kg)	1427	

\*The specifications are subject to change without notice.

COMPACT TRACTOR

SB36-47

**SHIBAURA**



**Important information**

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



**SHIBAURA EUROPE BV**  
 Begonialaan 7  
 NL - 6851 TE Huissen  
 T. 0031 (0)26 326 9999  
 F. 0031 (0)26 326 9990  
 E. info@shibaaura.com  
 I. www.shibaaura.com

Dealer:

### DASHBOARD



Easy to read control panel with all the important information.

### TIRES



Industrial-, agricultural- and turf tires

### ENGINE



The 3 cylinder diesel engine delivers the highest power in its class with outstanding durability and reliability. High-quality components guarantee a long service life.

### FRONT LIFT



Front lift cat. 1 with a lifting capacity of 1000 kg.



### 3-POINT HITCH



The category 1 hitch has a lift capacity of 1650 kg at the ball end.

### PEDALS



Hydrostatic control pedals for smooth hands free forward and reverse motion.

### CONTROL ELEMENT



Through the intuitive control element, attention can be focused entirely on the work.

### CABIN



High specification, factory fitted cabin with an ergonomic layout of the controls. Standard with air conditioning and radio.