

Specifications*

| MODEL | | SB36h | SB47h |
|--------------------------|----------|----------------------------------|------------|
| ENGINE (DIESEL) | | | |
| Model | | A1700N4 | A1700T2 |
| Type | | Water cooled 3-cylinder diesel | |
| Displacement | (cc) | 1714 | 1714 |
| Engine gross power | (HP/ kW) | 35/ 25.7 | 45.5/ 33.5 |
| Rated speed | (rpm.) | 2600 | |
| Fuel tank capacity | (l.) | 27 | |
| Combustion system | | Indirect | |
| Battery | (V.) | 12 | |
| Air cleaner | | Dry, element | |
| TRAVELLING SYSTEM | | | |
| Transmission | | Hydrostatic | |
| Groups | | 3 | |
| Max. forward speed | (km/h) | 33 | |
| Drive system | | 4 Wheel Drive | |
| Brake | | Wet, multidisc | |
| Sperdifferential | | Rear | |
| TIRES | | | |
| Agri | Front | ROPS: 8-16 / Cabin: 7-16 | |
| | Rear | ROPS: 12.4-24 / Cabin: 11,2 -24 | |
| Turf | Front | 27x8.5x15 | |
| | Rear | 41x14-20 | |
| Industry | Front | ROPS: 10x16.5 / Cabin: 24x8.5-14 | |
| | Rear | ROPS: 420/70-24 / Cabin: 15-19.5 | |
| PTO | | | |
| Rear PTO | (rpm.) | independent, 560 and 780 | |
| HYDRAULIC SYSTEM | | | |
| Main | (lpm.) | 33.6 | |
| Steering | (lpm.) | 18 | |
| Steering category | | Power Assisted Hydrostatic | |
| Control type | | Position / Draft | |
| Remote Control valve | | 1 double acting rear | |
| Hitch category | | Cat. 1 | |
| Max. lift capacity | (kg) | 1650 | |
| DIMENSIONS | | | |
| Length | (mm) | 3096 | |
| Width | (mm) | 1451 | |
| Height | (mm) | 2643 | |
| Ground clearance | (mm) | 335 | |
| Wheelbase | (mm) | 1671 | |
| Weight incl. ROPS | (kg) | 1427 | |

*The specifications are subject to change without notice.



Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



SHIBAURA EUROPE BV

Begonialaan 7

NL - 6851 TE Huissen

T. 0031 (0)26 326 9999

F. 0031 (0)26 326 9990

E. info@shibaura.com

I. www.shibaura.com

Dealer: