

Grasscollector



Options

Scrapers



Specifications*

MODEL		SR888
DIMENSIONS		
Length	(mm)	2750
Width	mowing	(mm) 2870
	transport	(mm) 2195
Height	(mm)	2100 (incl. ROPS)
Wheelbase	(mm)	1595
Tread width	front	(mm) 1735
	rear	(mm) 1150
Ground clearance	(mm)	160
Tires	front	24x12.00-12 4PR
	rear	20x8.00-10 4PR
Weight	(kg)	1550
MOTOR		
Model		Shibaura N844L
Type		water-cooled, diesel
Number of cylinders		4
Displacement	(cc)	2216
Horsepower/ rated speed	(DIN kW (HP) / rpm.)	33.6 (45) / 2700
Fuel tank capacity	(l.)	43
Battery		75D26L
TRANSMISSION		
Type		hydrostatic, 2 range high/ low, autom. 4WD or permanent 4WD
Brake		wet discs
Steering		hydraulic power steering
Travelling range	forward	2
	reverse	2
Travelling speed	forward	(km/h) L: 0 ~ 11.8 H: 0 ~ 17.1
	reverse	(km/h) L: 0 ~ 8.3 H: 0 ~ 11.9
FAIRWAY MOWER		
Total width of cut	(mm)	2500
Width of cut reel	(mm)	560
Reel diameter	(mm)	Ø 178
Number of reel		9-blade (standard), 7/ 11-blade (option)
Height of cut	(mm)	7 ~ 30

* We reserve the right to discontinue models or change specifications without notice.

Important information

• Improper use of any product may cause serious or fatal injury. Read, understand and follow carefully the operating and safety instructions in your owner's manual before using such products.



SHIBAURA EUROPE BV
 Begonialaan 7
 NL - 6851 TE Huissen
 T. (0031) 026 326 9999
 F. (0031) 026 326 9990
 E. info@shibaura.com
 I. www.shibaura.com

Dealer:



SHIBAURA

Lightweight and compact styling, excellent operator comfort and superb cutting performance. Low centre of gravity ensures stable performance over undulating ground, mechanical 4WD ensures excellent climbing capabilities without loss of power.

SR888

Width of cut: 2500 mm

Safety features

Mower revolution stops when lifting up reel mower.
Engine stops when operator leaves seat.



Operator comfort

Adjustable seat suspension, reclining seat and a tilt steering wheel ensure operator comfort.

Excellent visibility to reel mower

Tilting steering wheel

Adjustable seat suspension



Reclining seat

Sliding seat

Maintenance made easy - reduced service time

Access to all major components is made simple with tilting operator seat/ platform and full bonnet opening. Radiator can be cleaned easy by opening the front screen and retractable shutter.



Shibaura diesel engine

Equipped with Shibaura 45 HP diesel engine.



Easy operation

Ergonomically designed controls for ease of use.



Diverter valve

All cutting units are fitted with diverter valves enabling the back lap of individual units.



Cutting unit adjustment

Centre cutting units can be easily rotated and moved sideways to adjust the roller bracket position, cutting height and grass discharge cover.



Easy adjustable of cutting height

