

gsr ⊕

0

AR

gsr⊕ electric gtm⊕ electric

EN











Zero emissions Low noise Long autonomy




Gardening





GSR+ and GTM+ are professional electric mowers with lithium-ion battery. Designed to offer high performance, low noise and zero emissions, they are suited to the needs of both home users and professional maintenance operators. The GSR+ front mower ensures excellent mulching with rear discharge, wide visibility over the work area and precision trimming for impeccable results. The vertical positioning system of the deck allows easy access to the underside, simplifying maintenance and cleaning. The cutting height is conveniently adjustable from on-board the machine by means of a rocker button.





Battery: 120 Ah / 192 Ah 🕢 Speed: 10 km/h 🕔 Autonomy: 6-8 hours







The **small footprint** of the GTM+, in particular its 85 cm width, allows it to fit into **tight spaces and entrances**. Its small size is complemented by **comfort and convenience**. **Collector emptying is electrical**, pushbutton operated, and **the cutting height** of the rear mower can be **adjusted from on-board the machine** by means of a convenient lever.



Both models are equipped with a **speed management system during** cutting to **save battery power consumption and at** **the same time ensure better efficiency** when operating the blades.



Technical features

| Model | GSR + STANDARD RANGE | GSR + LONG RANGE |
|---------------------------|---|--|
| Battery | | |
| Type of battery | Lithium-ion 54 V 120 Ah 6,8 kWh | Lithium-ion 54 V 192 Ah 11 kWh |
| Charging time | 3,5 hours | 5,5 hours |
| Charging system | Integrated battery charger with cable | Integrated battery charger with cable |
| Autonomy | 6-8 hours depending on working conditions | 6-8 hours depending on working conditions |
| Transmission | | |
| Transmission type | Electrical | Electrical |
| Forward speed | 10 km/h | 10 km/h |
| Forward / Reverse motion | Single pedal operation | Single pedal operation |
| Driving wheels | 2WD, front traction | 2WD, front traction |
| Engine drive | Electric 1,2 kW | Electric 1,2 kW |
| Brakes | Electromagnetic on transmission engine with automatic drive | Electromagnetic on transmission engine with automatic drive |
| Steering | Mechanical steering | Mechanical steering |
| Cutting system | | |
| Type of cutting | Mulching with possible rear discharge | Mulching with possible rear discharge |
| Cutting width | 112 cm | 112 cm |
| Blades | Three-blade deck | Three-blade deck |
| Blade engine | Electrical 9 kW | Electrical 9 kW |
| Cutting height adjustment | Electrical push-button | Electrical push-button |
| Deck verticalisation | Mechanical and electrical with use of a lever and a button | Mechanical and electrical with use of a level and a button |
| Dimensions and weight | | |
| Front wheels | 16×7.50-8 | 16×7.50-8 |
| Rear wheels | 140-6 | 140-6 |
| Length / Width / Height | 255×112×135 cm | 255×112×135 cm |
| Weight empty | 375 kg | 395 kg |
| | | |







1100



all and a second

3 March the states

\$ 15

Ð

qsr_€

STATISTICS OF

ANNAN AN

031

Technical features

| Model | GTM + STANDARD RANGE | GTM + LONG RANGE |
|---------------------------------------|---|---|
| Battery | | |
| Type of battery | Lithium-ion 54 V 72Ah 4Kwh | Lithium-ion 54 V 144Ah 8 Kwh |
| Charging time | 2 hours | 4 hours |
| Charging system | Integrated battery charger with cable | Integrated battery charger with cable |
| Autonomy | 6-8 hours depending on working conditions | 6-8 hours depending on working conditions |
| Transmission | | |
| Transmission type | Electrical | Electrical |
| Forward speed | 10 km/h | 10 km/h |
| Forward / Reverse motion | Single pedal operation | Single pedal operation |
| Driving wheels | 2WD, rear wheel drive | 2WD, rear wheel drive |
| Engine drive | Electric 1,2 kW | Electric 1,2 kW |
| Brakes | Electromagnetic on transmission engine with automatic drive | Electromagnetic on transmission engine with automatic drive |
| Steering | Mechanical steering | Mechanical steering |
| Cutting system | | |
| Type of collection | Direct, midmount mower, rear or side discharge | Direct, midmount mower, rear or side discharge |
| Collector capacity and attachments | 280 litres, full collector warning buzzer | 280 litres, full collector warning buzzer |
| Collector emptying | Electrical push-button operated | Electrical push-button operated |
| Cutting width | 80 cm | 80 cm |
| Blades | Single blade with shock-absorbing floating blades | Single blade with shock-absorbing floating blades |
| Blade engine | Electrical 3 kW | Electrical 3 kW |
| Cutting height adjustment | Manual with use of a lever | Manual with use of a lever |
| Dimensions and weigl | ht | |
| Front wheels | 13×5.00-6 | 13×5.00-6 |
| Rear wheels | 16×7.50-8 | 16×7.50-8 |
| Length / Width / Height | 202×85×122 cm | 202×85×122 cm |
| Weight empty | 266 kg | 286 kg |
| | | |







SIDE DISCHARGE KIT

GTM+ Electric also allows cutting with side discharge by making a slight variation in deck opening.

MULCHING CLOSURE

The addition of a protective blade/closing the loading channel and removing the plastic shaped bottom of the collector also allow the operator to use the rear discharge.





gianniferrari.com

